

Ordering example: 4 x KP-20000-125

Order No.	S <sup>(1)</sup> mm	L mm	A mm	F <sub>0</sub> <sup>(2)</sup> daN (20°C, 150 bar)	F daN	<sup>(3)</sup> kg
KP-20000-19	19	148	129	20000	28200	No 22.63
KP-20000-25	25	160	135		29500	No 23.16
KP-20000-32	32	174	142		30700	No 23.76
KP-20000-38	38	186	148		31500	No 25.66
KP-20000-50	50	210	160		32700	No 27.31
KP-20000-63	63	236	173		39200	No 28.02
KP-20000-75	75	260	185		39200	No 29.53
KP-20000-80	80	270	190		39200	No 31.45
KP-20000-100	100	310	210		39200	No 32.70
KP-20000-125	125	360	235		39200	No 35.30






<sup>(1)</sup> other strokes under request

<sup>(2)</sup> alternative forces upon request




Pressure medium	N <sub>2</sub>	Working temperature	0-80°C	Min. security stroke	10%
Max. Charging pressure	150 bar	Temperature related force increase	+0.34%/°C	Repair Kit	KIT KP-20000
Min. Charging pressure	25 bar	Max. working speed	1.6 m/s	Linkable	G1/8"

### Mounting possibilities




## Flanges


**BFE-10000**




**BFI-10000**




**GR-10000**



**AR-10000**



**XS-10000**



**XC-10000**

