

Ordering example: 4 x HD-20000-125

Order No.	S ⁽¹⁾ mm	L mm	A mm	F ₀ ⁽²⁾ daN (20°C, 150 bar)	F daN	⁽³⁾ Linkable	kg
HD-20000-25	25	210	185	20000	26000	No	28.75
HD-20000-38	38	236	198		27600	No	31.68
HD-20000-50	50	260	210		29000	No	33.47
HD-20000-63	63	286	223		29700	No	35.02
HD-20000-80	80	320	240		30700	No	39.6
HD-20000-100	100	360	260		31500	No	40.34
HD-20000-125	125	410	285		32200	No	43.5
HD-20000-160	160	480	320		33000	No	46.58
HD-20000-200	200	560	360		33500	No	51.23
HD-20000-250	250	660	410		34200	No	70.2
HD-20000-300	300	760	460	35000	No	76.62	






⁽¹⁾ other strokes under request

⁽²⁾ alternative forces upon request




Pressure medium	N ₂	Working temperature	0-80°C	Min. security stroke	10%
Max. Charging pressure	150 bar	Temperature related force increase	+0.34%/°C	Repair Kit	KIT HD-20000
Min. Charging pressure	25 bar	Max. working speed	1.6 m/s	Linkable	G1/8"

Mounting possibilities




Flanges


BFE-10000




BFI-10000




GR-10000



AR-10000



XS-10000



XC-10000

