

Ordering example: 4 x TSC-4700-65

Order No.	S <sup>(1)</sup> mm	L mm	A mm	F <sub>0</sub> <sup>(2)</sup> daN	F daN	(3)	kg
TSC-4700-10	10	100	90	4700 (20°C, 150 bar)	6800	No	2.11
TSC-4700-16	16	126	110		6800	No	2.36
TSC-4700-25	25	155	130		7000	No	2.63
TSC-4700-32	32	187	155		6800	No	2.94
TSC-4700-40	40	220	180		6800	No	3.28
TSC-4700-50	50	260	210		6800	No	2.70
TSC-4700-65	65	293	228		7000	No	3.98

other strokes <sup>(1)</sup> under request






alternative forces <sup>(2)</sup> upon request

ESK <sup>(3)</sup> under request




Pressure medium	N <sub>2</sub>	Working temperature	0-80°C	Min. security stroke	10%
Max. Charging pressure	150 bar	Temperature related force increase	+0.34%/°C	Repair Kit	KIT TSC-4700
Min. Charging pressure	25 bar	Max. working speed	0.5 m/s	Linkable	G1/8"

### Mounting possibilities




## Flanges


**BFE-1500**




**BFI-1500**



**MC-2500**




**GR-1500**



VDI



**MT-2500**



**XCS-4700**

